## II. <u>List of all Pending Claims</u>

1. (Currently amended) A device used to accept an operator input to a computing device, comprising:

a first layer which includes a translucent cover;

a second layer which includes a plurality of surfaces, said surfaces being one of a capacitive or resistive surface and being constructed using a translucent and conductive material; and

a third layer which includes a light-emitting material which generates light in response to said operator input: and

<u>a fourth layer which generates light of a different color than light generated</u> <u>by said third layer.</u>

- 2. (Original) The device of claim 1 wherein said operator input is one of a user's finger and thumb positioned at a location near a side of said first layer, said side being opposite said second layer, said operator input being used to control an aspect of a computer display controlled by said computing device.
- 3. (Original) The device of claim 2 wherein said control of said aspect of said computer display is conveyed through a wireless link between said device and said computing device.
- 4. (Original) The device of claim 2 wherein said control of said aspect of said computer display is conveyed through a wire line link between said device and said computing device.
- 5. (Original) The device of claim 2 wherein said plurality of surfaces function by responding to changes in capacitance between adjacent ones of said plurality of surfaces.



- 6. (Original) The device of claim 1 wherein said operator input is one of a user's finger and thumb applying pressure to said first layer, said pressure being used to control an aspect of a computer display associated with said computing device.
- 7. (Original) The device of claim 6 wherein said plurality of surfaces function by responding to changes in resistance between adjacent ones of said plurality of surfaces.
- 8. (Original) The device of claim 1 wherein said plurality of surfaces is constructed using a material which is transparent.

9. Canceled

(Original) The device of claim 1 wherein said computing device launches a software application that runs on said computing device in response to said operator input.

(Original) The device of claim 1 wherein said light-emitting material generates light that persists for a period of time after one of a user's finger and thumb has been positioned at a location on the top side of said first layer, said light being generated only in an area proximate to said location.

(Original) The device of claim 1 wherein said light-emitting layer generates light that persists for a period of time after one of a user's finger and thumb has been positioned at a location on the top side of said first layer, said light being generated in areas other than an area proximate to said location.

13. (Original) The device of claim 1 wherein said light-emitting material is an electroluminescent material.

(Original) The device of claim 1 wherein said light-emitting material is a light-emitting diode.

(Original) The device of claim 1, wherein said first, second, and third layers are substantially two-dimensional.

(Original) The device of claim 1, wherein said operator input is a character entered on said translucent cover and said generated light forms a trace of said character.

(Original) The device of claim 1, wherein said generated light presents the appearance of soft keys.

(Currently amended) A computing device that makes use of a touch pad to provide feedback to a user, said feedback being indicative of an operating mode of at least one input device used by said computing device, comprising:

a first layer which includes a substantially rigid, transparent surface;

a second layer which includes a plurality of surfaces proximate with said first layer, said plurality of surfaces being constructed of a transparent and conductive material;

a third layer which includes a light-emitting layer, said third layer generating light in response to an operator input, and wherein said light-emitting layer is arranged to present a particular symbol to said user; and

an illumination controller coupled to said third layer for bringing about said light generated in response to said operator input.

19. Canceled

(Original) The computing device of clam wherein said third layer additionally notifies said user that said operator input is required.

(Original) The computing device of claim 20 wherein said touch pad additionally receives said operator input.

(Original) The computing device of claim wherein said operator input is a user selecting to use said touch pad to control an aspect of a display coupled to said computing device.

23. (Original) The computing device of claim 22 wherein said aspect of said display is a position of a cursor on said display.

24. (Original) The computing device of claim 22 wherein said aspect of said display is a scroll bar used in a window of said display.

25. (Original) The computing device of claim wherein said plurality of surfaces functions by responding to changes in capacitance of elements of said plurality of surfaces.

26. (Original) The computing device of claim 16 wherein said operator input is conveyed by way of a wireless interface between said computing device and said touch pad.

27. (Original) The computing device of claim 8 wherein said computing device is a laptop computer.

28. (Original) The computing device of claim 18 further comprising a selector which influences an operating state of said illumination controller.

(Original) The computing device of claim to further comprising a fourth layer which generates light of a different color than said light generated by said third layer, said fourth layer generating light in response to said operator input, said fourth layer also being coupled to said illumination controller for bringing about said light generated in response to said operator input.

5

(Original) The computing device of claim 29 wherein said fourth layer covers an area of said touch pad that is substantially less than the area covered by said third layer.

(Original) The computing device of claim 29 further comprising a selector which activates said third and said fourth layer, thereby allowing said light generated by said third and said fourth layers to be combined to form light of a different color than said third layer and different than said fourth layer.

Please cancel claims 32-39.